

# TRANTEX MODEL CH360SP

## SELF-PROPELLED EXTRUSION THERMOPLASTIC APPLICATOR



**NOW WITH  
ELECTRIC START!**

### STANDARD EQUIPMENT


- SELF PROPULSION SYSTEM** • Hydrostatic drive allows infinite speeds, forward and reverse, of up to 4 mph (7 kph).
- DRIVE ENGINE** • 5.5 HP propane fired Honda with electric start.
- ALL STEEL EXTRUSION DIES** • Heat treated steel, not aluminum. No drip, clean cut on/off operation. Improved push/ pull mechanism eliminates die springs. Dies available in numerous widths : 4",5",6",8",12",16", 18" dual 4", and dual 6".
- VARIABLE WIDTH GLASS BEAD SYSTEM** • Bead hopper capacity of 60 lbs. Adjustable widths of 4", 8", 12", and dual 4".
- 360 LB. MATERIAL TANK CAPACITY** • Removable/interchangeable for quick color changes. Larger capacity 500 lb. material tank available.
- POINTER SYSTEM** • Adjustable, lift/lower.
- HAND TORCH** • Standard for numerous operations.
- TOOL KIT** • For routine maintenance.



Shown with optional riding operator's sulky.

### OPTIONAL EQUIPMENT

- AUTOMATIC AGITATION** • Provides automatic constant agitation of material.
- OPERATOR'S SULKY** • Adjustable padded seat provides additional propane storage. Can be removed in seconds for detail work. Includes unique steering system that allows for straight steering or preset radii in curves.
- AUTOMATIC THERMOSTAT** • Regulates material temperature automatically.
- EXTRA MATERIAL TANK** • Allows on the spot color changes.
- LARGER MATERIAL TANK** • Larger capacity 500 lb. material tank available.
- BITUMINOUS TANK** • 300 lb. capacity with one dispensing valve for installing pavement markers or traffic buttons.
- DOUBLE DROP GLASS BEAD SYSTEM** • For improved luminosity.
- COMPACT SIZE** • L-51" X W-30" X H-44"



Optional automatic agitation.

**SPRAY AND PROFILE APPLICATION VERSIONS AVAILABLE!**

*Trantex supplies a complete line of thermoplastic and paint equipment and materials. Contact us today for a free catalog!*