

■ Traffic Signaling Products



MRA-6LC-6 Modular Vehicle Loop Detector

The **MRA-6LC-6** is a modular device utilizing solid state Silicon foldover technology.

The **MRA-6LC-6** is designed for any traffic controller cabinet equipped with 6 position, 5.08 mm spacing sockets wired in line with load relay outputs.

SPECIFICATIONS

Operating Voltage	75 VDC
Clamping Voltage	130 VDC
Operating Current	NA
Peak Surge Current	250 A
SPD Technology	Silicon Breakover Device
Connection Type	6 position 5.08mm Euroblock
Operating Temperature	-40 C to +85 C
Dimensions (Inches)	2H x 0.7W x 1.5L
Weight	2 oz


INSTALLATION

One MRA-6LC-6 is used for each two loop detectors to be protected.

Units are installed as close as practical to the point where the detector loop wires enter the controller cabinet.

CAUTION: Installation and service should be performed by qualified technicians or service personnel.

**Keeping
You
Connected!**



**NEED HELP?
Call 1-800-648-4076**

1805 N.E. 19th Avenue
P.O. Box 1778
Ocala, Florida 34478
(352) 732-3029
FAX (352) 867-1237
Sales: 1-800-648-4076
E-mail us at:
edco@edcosurge.com
Internet:
<http://www.edcosurge.com>

EMERSON
Network Power